

UNCLASSIFIED

AD NUMBER

AD518306

CLASSIFICATION CHANGES

TO: unclassified

FROM: confidential

LIMITATION CHANGES

TO:

Approved for public release, distribution unlimited

FROM:

Distribution limited to U.S. Gov't. agencies only; Test and Evaluation; Nov 1971. Other requests for this document must be referred to Director, Naval Research Lab., Washington, D.C. 20390. NOFORN.

AUTHORITY

NRL ltr, 22 Aug 2002; NRL ltr, 22 Aug 2002

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD NUMBER
AD518306
CLASSIFICATION CHANGES
TO confidential
FROM secret
AUTHORITY
30 Nov 1983, per document marking, DoDD 5200.10

THIS PAGE IS UNCLASSIFIED

SECRET-NOFORN

NRL Memorandum Report 2360
Copy No. 2 of 8 Copies

**The Effectiveness of
Infrared Suppression Techniques
in Reducing the Vulnerability
of the F-4 Aircraft
to the ATOLL Missile**
[Unclassified Title]

H. TOOTHMAN, R. LISTER, AND C. LOUGHMILLER


*Airborne Radar Branch
Radar Division*

November 1971

**SPECIAL HANDLING REQUIRED
NOT RELEASABLE TO FOREIGN NATIONALS**



**NAVAL RESEARCH LABORATORY
Washington, D.C.**



SECRET-NOFORN

Downgraded at 12 year intervals.
Not automatically declassified.

AD NO. AD 518306
DDC FILE COPY

4

2

B

L

See form 1473

SECRET-NOFORN

SECURITY

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

SECTION FOR	
TESTI	WHITE SECTION <input type="checkbox"/>
DOC	DIFF SECTION <input checked="" type="checkbox"/>
UNANNOUNCED	
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY	
DISC.	APPROV. BY
B	

SECRET-NOFORN

SECRET NOFORN

ABSTRACT (S)

Five IR suppression techniques were examined to determine their effectiveness in reducing the vulnerability of the F-4 aircraft to the ATOLL missile. Two of these techniques, both using IR dispersive clouds, significantly reduced ATOLL performance. ATOLL launch zones are given for three non-maneuvering and four maneuvering tactical conditions.

AUTHORIZATION

53D01-03
A05-510-112/652-1/W 16-140-02

TABLE OF CONTENTS

Abstract	i
Authorization	i
Table of Contents	ii
I. Introduction	1
II. Computer Representation	1
III. IR Suppression Models	2
A. Suppression Techniques	2
B. Computer Model	2
IV. ATOLL Performance	3
A. Non-Maneuvering F-4	3
B. Maneuvering F-4	3
V. Conclusions	4
VI. Recommendations	4
References	5
Distribution List	15

I. INTRODUCTION

(C) The ATOLL (AA-2), a Soviet copy of the Sidewinder missile, poses a significant threat to U.S. aircraft. One way of reducing the ATOLL threat is to reduce its launch zone by reducing the target aircraft's IR radiation in the ATOLL seeker bandpass. This report is a study of the effectiveness of techniques for reducing the IR output of the F-4 aircraft at military power.

(S) Several problems must be considered when attempting to decrease the vulnerability of an aircraft to a missile. At altitudes below 15K feet the ATOLL is aerodynamically limited while engaging an F-4 on military power. In this case, to reduce the ATOLL launch zone by reducing IR output of the aircraft, the IR output must first be reduced to where the IR limit equals the aerodynamic limit. Further reduction of IR output must now be made to reduce the ATOLL launch zone. The effect of these further reductions will follow the inverse square law, i.e., a four-fold reduction of IR energy output is required to reduce ATOLL range by a factor of two.

(U) A digital simulation of the ATOLL has been used to determine the countermeasures effectiveness of IR reduction techniques developed by General Electric (GE). The IR signatures estimated by GE are used in the simulation. The results of many simulated trajectories are combined to determine launch zones for the ATOLL for each IR signature supplied by GE.

II. COMPUTER REPRESENTATION

(C) A four-degree-of-freedom model of the F-4 aircraft and a six-degree-of-freedom model of the ATOLL have been constructed at the Naval Research Laboratory (NRL). The thrust, drag, and lift characteristics of the F-4 were included to assure realistic simulation of maneuvers. The IR signature of the F-4, atmospheric attenuation formulas, and ATOLL detector sensitivity measurements were used to develop the IR signal model. ATOLL tracking error data were combined with a Sidewinder LA tracking model for the missile guidance characteristics. Sidewinder LA gas servo performance data are included in the guidance and autopilot model. Tables of aerodynamic moments, along with normal and axial forces, for the ATOLL are used in the computer program to calculate the missile response. Data used in the development of the missile model were supplied by Naval Weapon Center (NWC), China Lake. A full description of the missile model and the F-4 aerodynamic model is found in (1).

III. IR SUPPRESSION MODELS

A. Suppression Techniques

(S) General Electric (Evendale, Ohio) has made theoretical studies and ground measurements of possible IR suppression retrofits to the J-79-10 and J-79-17 engines used in the F-4. The effects of centerbody cooling, tailpipe cooling, and fuel and oil cloud generation on the IR signal of the J79 are described in (2). Subsequent to (2), GE suggested that a titanium dioxide (TiO_2) cloud would be highly effective in reducing the J79 IR emissions. Also subsequent to (2), GE revised their estimate of practical component cooling from $1200^\circ R$ to $1400^\circ R$ and revised the IR data accordingly. These revised IR signature estimates, as well as an estimate of the signature through a TiO_2 cloud, were used in this study.

(S) Five suppression techniques were selected for comparison with the standard (unmodified) engine. The models used in this study are 1) the unsuppressed J79, 2) a "7808" oil cloud, 3) centerbody and tailpipe cooled to $1400^\circ R$, 4) tail-pipe only cooled to $1400^\circ R$, 5) centerbody only cooled to $1400^\circ R$, and 6) centerbody and tailpipe cooled to $1400^\circ R$ plus a titanium dioxide cloud. Model 1 was chosen as a reference for each of the techniques. Model 2 was chosen because it represents a minimum of modification, development, and weight penalty. Models 3, 4, and 5 are covert techniques. Model 6 represents the best technique for IR suppression used in this study.

B. Computer Model

(S) The IR signatures used in the computer model are given in Table 1. Since the data supplied by GE, (2), were for only one J79 engine, it was assumed that the total F-4 emission would be twice that for a single engine. Thus the data in Table 1 are twice the values of IR radiant intensity given by GE. Since GE calculations are for the total radiant intensity in the 1.7 to 2.95 micron band, it is necessary to reduce these values during the simulation to account for the ATOLL's spectral response in this band. Calculations show that the ATOLL sees 65% of the total energy of a blackbody in the 1.7 to 2.95 micron band at normal J79 tailpipe temperature. The 35% signal loss was applied to the F-4 signatures of Table 1.

(U) Atmospheric attenuation of the signal is also based on normal tailpipe temperature blackbody spectral characteristics. The band pass of the ATOLL seeker is broken into 0.1 micron intervals. This enables a more accurate calculation of how tailpipe energy in the IR spectrum is attenuated as a function of range. The calculations, based upon a blackbody at $350^\circ K$, were performed at several ranges and altitudes. The loss in decibels is given in Table 2. The assumption of normal

tailpipe temperature spectral response was made necessary because the spectral characteristics of the various suppression techniques were not available. No tailpipe shielding effects were used in this study.

IV. ATOLL PERFORMANCE

A. Non-Maneuvering F-4

(C) The non-maneuvering launch envelopes for the ATOLL engaging an F-4 aircraft with 3 altitude-speed combinations are given on Figures 1, 3, and 6. There are no arbitrary restrictions on the envelope. That is, if a missile is launched within the envelope it will come within 25 feet of the center of mass of the F-4. In particular, no criterion is used to judge whether or not the enemy pilot can tell if the ATOLL is capable of tracking the F-4. Under certain conditions an initial signal-to-noise ratio of less than 2 is sufficient for the ATOLL to guide successfully. There is some question whether the pilot can detect such signal against typical background noise. Thus the overall system effectiveness envelopes may be significantly smaller than the missile envelope presented here.

(S) The envelopes on Figure 1 show that at 5K feet altitude the ATOLL is essentially aerodynamically limited. Thus, only at large angles off the F-4 tail (where the ATOLL is normally IR energy limited) are there significant differences shown for the various suppression techniques. The situation is much the same at 15 K feet altitude except that the oil drop cloud has a marginal effectiveness. At low altitudes only the TiO_2 cloud significantly reduces ATOLL launch envelopes. The reductions of the launch zone area due to the TiO_2 cloud as shown on Figures 1 and 3 are about 75% and 85% respectively.

(SNF) At 30K feet, as shown on Figure 6, the oil drop cloud is fairly effective and the TiO_2 cloud is very effective. The component cooling techniques were not significantly effective in the non-maneuvering target situations. Thus the moderate cooling assumed in the IR models used in this study does not provide a useful covert IRCM technique. However, such cooling may be useful in conjunction with pulsed jammers, since it permits lower power IR transmitters. The TiO_2 cloud is very effective if it can be generated before the ATOLL is launched. This implies either a technique to warn the F-4 when an ATOLL attack is imminent, or a continuous generation of the cloud. The cloud is likely to be highly visible in daylight and thus is unsuitable for use except when the F-4 is under ATOLL attack.

B. Maneuvering F-4

(SNF) As shown in Figures 2, 4, 5 and 7, the ATOLL launch zones are reduced significantly by maneuvers of the F-4. However, only the TiO_2 cloud significantly reduces the size of the maneuvering F-4

SECRET NOFORN

ATOLL launch envelopes under all conditions studied. The oil cloud is effective at 30K feet altitude but relatively ineffective at lower altitudes. The use of TiO_2 in air combat maneuvering situations may be valuable. Although the cloud trail would be useful to the enemy for acquisition and tracking, it is possible that he might not be able to press a successful attack into the more restricted launch zones.

V. CONCLUSIONS

1. (S) The component-cooling models which were studied are ineffective ATOLL countermeasures.

2. (S) A cloud of TiO_2 particles has significant countermeasure potential.

VI. RECOMMENDATIONS

1. (C) Studies or tests to determine the minimum signal that may be detected by the pilot of the ATOLL aircraft should be initiated.

2. (S) Instrumented flight tests to determine the IR suppression characteristics of TiO_2 (or similar) clouds should be initiated.

3. (SNF) Detailed studies to determine the usefulness of component cooling in conjunction with pulsed IR jammers should be initiated.

SECRET NOFORN

REFERENCES

1. H. Toothman, C. Loughmiller, and R. Lister, "The Effect of F-4B Maneuvers on ATOLL (AA-2) Performance," NRL MR 1989, Secret Noform, 1969.
2. R.E. Latta, T. Loftus, and C.M. Stanforth, "Interim Status Report on the General Electric J79 IR Suppression Program," R69AEG 415, Secret, October 1969.

TABLE 1 (S)

F-4 Infrared Radiant Intensity (twice J79 Intensity)
in 1.7-2.95 Micron Band (watts/steradians)

Altitude	Angle off engine axis deg.	IR Model Number					
		1	2	3	4	5	6
5K ft	0	594	44	448	594	448	16
	5	820	54	698	818	690	22
	10	876	58	805	845	839	26
	25	494	152	292	292	494	45
	45	90	130	90	90	90	65
	60	40	40	40	40	40	20
	90	20	34	20	20	20	17
15K ft	0	642	48	474	642	476	18
	5	876	58	733	874	733	24
	10	930	60	857	902	871	28
	25	516	158	306	306	516	47
	45	56	130	56	56	56	65
	60	44	40	44	44	44	20
	90	20	34	20	20	20	17
30K ft	0	526	40	385	526	385	15
	5	724	48	604	723	605	20
	10	772	50	716	747	742	24
	25	412	126	245	245	411	38
	45	42	130	42	42	42	65
	60	32	40	32	32	32	20
	90	20	34	20	20	20	17

SECRET

Table 2 (U)

Blackbody (~850°K) IR Atmospheric Attenuation
in the ATOLL Bandpass (decibels)

Altitude (K ft)	Range (ft)				
	1,000	3,000	6,000	12,000	24,000
0	2.33	3.66	4.15	4.51	4.91
10	1.70	2.45	2.95	3.51	3.99
20	0.89	1.32	1.70	2.22	2.69
30	0.35	0.65	0.90	1.05	1.41
40	0.14	0.28	0.42	0.57	0.73
50	0.01	0.14	0.21	0.28	0.42
60	0.00	0.01	0.07	0.21	0.28
70	0.00	0.00	0.01	0.07	0.14





Fig. 1 (S) - F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)






Fig. 3 (S) - F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)

ALTITUDE - 15,000 ft
 TARGET SPEED - M 0.9
 LAUNCH SPEED - M 1.2

1. NO IR SUPPRESSION
2. 7808 OIL CLOUD
3. TAILPIPE + CENTERBODY COOLED TO 1400° R
4. TAILPIPE COOLED TO 1400° R
5. CENTERBODY COOLED TO 1400° R
6. TAILPIPE + CENTERBODY COOLED TO 1400° R AND TIO₂ CLOUD (ESTIMATED)

SECRET




Fig. 4 (S) - F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)





Fig. 5 (S) - F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)



SECRET

ALTITUDE - 30,000 ft
 TARGET SPEED - M 0.9
 LAUNCH SPEED - M 1.5

1. NO IR SUPPRESSION
2. 7808 OIL CLOUD
3. TAILPIPE - CENTERBODY COOLED TO 1400° R
4. TAILPIPE COOLED TO 1400° R
5. CENTERBODY COOLED TO 1400° R
6. TAILPIPE - CENTERBODY COOLED TO 1400° R AND TiO₂ CLOUD (ESTIMATED)

Fig. 6 (S) F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)

SECRET

SECRET




Fig. 7 (S) - F-4 IR SUPPRESSION EFFECTIVENESS AGAINST THE ATOLL (U)

SECRET

SECRET - NOFORN
Security Classification

DOCUMENT CONTROL DATA - R & D

Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified

1. ORIGINATING ACTIVITY (Corporate author) Naval Research Laboratory Washington, D.C. 20390		2a. REPORT SECURITY CLASSIFICATION Secret - NoforN	
		2b. GROUP 3	
3. REPORT TITLE 6 THE EFFECTIVENESS OF INFRARED SUPPRESSION TECHNIQUES IN REDUCING THE VULNERABILITY OF THE F-4 AIRCRAFT TO THE ATOLL MISSILE (U) 3			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) A Final report on this phase of the problem. (Final Report)			
5. AUTHOR(S) (First name, middle initial, last name) 10 H. Toothman, R. Lister, and C. Loughmiller			
6. REPORT DATE 10 November 1971		7a. TOTAL NO. OF PAGES 12 22 p.	7b. NO. OF REFS 2
8. CONTRACT OR GRANT NO. 12 NRL 53 D01-03 A05-510-112/652-1/W16-140-02		9a. ORIGINATOR'S REPORT NUMBER(S) NRL Memorandum Report 2360 14 NRL-MR-2360	
9b. OTHER REPORT NUMBER (Any other numbers that may be assigned this report)			
10. DISTRIBUTION STATEMENT Distribution limited to U.S. Government Agencies only; test and evaluation, November 1971. Other requests for this document must be referred to the Director, Naval Research Laboratory, Washington, D.C. 20390.			
11. SUPPLEMENTARY NOTES Special Handling Required Not Releasable to Foreign Nationals		12. SPONSORING MILITARY ACTIVITY Naval Air Systems Command Department of the Navy Washington, D.C.	
13. ABSTRACT (Secret) Five IR suppression techniques were examined to determine their effectiveness in reducing the vulnerability of the F-4 aircraft to the ATOLL missile. Two of these techniques, both using IR dispersive clouds, significantly reduced ATOLL performance. ATOLL launch zones are given for three non-maneuvering and four maneuvering tactical conditions. ↑			

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Infrared suppression techniques Vulnerability of F-4 aircraft to ATOLL missile IR dispersive clouds						

Naval Research Laboratory
Technical Library
Research Reports Section

DATE: August 22, 2002
FROM: Mary Templeman, Code 5227
TO: Code 5300 Paul Hughes
CC: Tina Smallwood, Code 1221.1 *to 8/19/03*
SUBJ: Review of NRL Reports

Dear Sir/Madam:

Please review NRL Memo Reports 2139, 2150, 2170, 2297, 2360, 2425, 2426 and 2429 for:

- Possible Distribution Statement
- Possible Change in Classification

Thank you,



Mary Templeman
(202)767-3425
maryt@library.nrl.navy.mil

The subject report can be:

- Changed to Distribution A (Unlimited)
- Changed to Classification _____
- Other:

Paul H. Hughes IV 8/18/2003
Signature Date

-- 1 OF 1
-- 1 - AD NUMBER: 518306
-- 2 - FIELDS AND GROUPS: 17/4.4, 17/5.1, 15/3.1, 17/7.3
-- 3 - ENTRY CLASSIFICATION: UNCLASSIFIED
-- 5 - CORPORATE AUTHOR: NAVAL RESEARCH LAB WASHINGTON D C
-- 6 - UNCLASSIFIED TITLE: THE EFFECTIVENESS OF INFRARED SUPPRESSION
-- TECHNIQUES IN REDUCING THE VULNERABILITY OF THE F-4 AIRCRAFT TO THE
-- ATOLL MISSILE.
-- 8 - TITLE CLASSIFICATION: UNCLASSIFIED
-- 9 - DESCRIPTIVE NOTE: FINAL REPT.,
-- 10 - PERSONAL AUTHORS: TOOTHMAN,H. ;LISTER,R. ;LOUGHMILLER,C. ;
-- 11 - REPORT DATE: NOV 1971
-- 12 - PAGINATION: 22P MEDIA COST: \$ 7.00 PRICE CODE: AA
-- 14 - REPORT NUMBER: NRL-MR-2360
-- 16 - PROJECT NUMBER: NRL-53D01-03, A05-510-112/652-1/W16-140-02
-- 20 - REPORT CLASSIFICATION: CONFIDENTIAL
-- 22 - LIMITATIONS (ALPHA): DISTRIBUTION LIMITED TO U.S. GOV'T.
-- AGENCIES ONLY; TEST AND EVALUATION; NOV 71. OTHER REQUESTS FOR
-- THIS DOCUMENT MUST BE REFERRED TO DIRECTOR, NAVAL RESEARCH LAB.,
-- WASHINGTON, D. C. 20390.
-- 23 - DESCRIPTORS: (*INFRARED RADIATION, REDUCTION), (*GUIDED
-- MISSILE COUNTERMEASURES, HEAT HOMING), (*AIRCRAFT DEFENSE SYSTEMS,
-- GUIDED MISSILE COUNTERMEASURES), JET FIGHTERS, THREAT EVALUATION,
--
-- USSR, AIR TO AIR MISSILES, GUIDED MISSILE SIMULATORS, COMPUTER
-- PROGRAMS, VULNERABILITY
-- 24 - DESCRIPTOR CLASSIFICATION: UNCLASSIFIED
-- 29 - INITIAL INVENTORY: 2
-- 32 - REGRADE CATEGORY: C
-- 33 - LIMITATION CODES: 3
-- 34 - SOURCE SERIES: F
-- 35 - SOURCE CODE: 251950
-- 36 - ITEM LOCATION: DTIC
-- 38 - DECLASSIFICATION DATE: OADR
-- 40 - GEOPOLITICAL CODE: 1100
-- 41 - TYPE CODE: N
-- 43 - IAC DOCUMENT TYPE:
-- 49 - AUTHORITY FOR CHANGE: S TO C GP-3

APPROVED FOR PUBLIC
RELEASE - DISTRIBUTION
UNLIMITED